

Features					
	3390	3391	3392	3395	3397
True RMS measurements		*	*	*	*
Digital display counts	4000	4000	4000	6000	50000
Electronic overload protection	*	*	*	*	*
Analog Bargraph/segments			* /41	* /61	* /51
Continuity buzzer & Diode check	*	*	*	*	*
Data Hold function	*	*	*	*	*
Peak Hold function			*	Min./Max.	*
Inrush current measurement					*
DCA Zero function			*	*	*
Auto Power Off	*	*	*	*	*
Low battery indication	*	*	*	*	*
AC/DC Current	AC	AC	*	*	*
2" (52mm) Clamp jaw opening	*	*	*	*	*
NCV Detection	*	*	*	*	*

1

Specifications								
Function	Max Range	Basic Accuracy	Max. Resolution	3390	3391	3392	3395	3397
AC Current	1000 A	$\pm(2.5\%+5d)$	10mA	*	*	*	*	*
DC Current	1000 A	$\pm(3.0\%+4d)$	10mA			*	*	*
AC Voltage	600V	$\pm(0.8\%+2d)$	0.1mV	*	*	*	*	*
DC Voltage	600V	$\pm(1.0\%+4d)$	0.1mV	*	*	*	*	*
Resistance	40M Ω	$\pm(1.0\%+4d)$	0.1 Ω	*	*	*	*	50mF
Capacitance	40mF	$\pm(3.0\%+5d)$	0.01nF	100 μ F	100 μ F	*	4000 μ F	10mF
Frequency	10MHz	$\pm(1.2\%+3d)$	0.01MHz	*	*	4kHz	*	*
Temperature	1000°C/1832°F	$\pm(3.0\%+5d)$	1°C/°F		*	*	*	*